

MINI SPLIT (2026)



ESPECIFICACIONES TÉCNICAS:

Model No.		12K CO	18K CO	24K CO		
System	Type	Cooling only				
	Control type	Remote				
	Rated cooling capacity	Btu/h	12,000	18,000	24,000	
	Rated heating capacity	Btu/h	N.A	N.A	N.A	
	EER for cooling	W/W	2.73	2.74	2.85	
	COP for heating	W/W	N.A	N.A	N.A	
	Moisture removal	Liters/h	1.2	1.8	2.2	
	Pressure	High(DP)	MPa	4.5	4.5	4.5
		Low(SP)	MPa	1.9	1.9	1.9
	Indoor noise level at cooling	High	dB(A)	41	44	50
Med.		dB(A)	38	40	46	
Low		dB(A)	34	36	42	
Outdoor noise level	dB(A)	51	55	62		
Electrical Data	Power supply	208-230V~/60Hz/1P				
	Voltage Range	V	198~253	198~253	198~253	
	Rated current	Cooling	A	6.1	9.2	11.7
		Heating	A	N.A	N.A	N.A
	Rated input	Cooling	W	1288	1925	2470
		Heating	W	N.A	N.A	N.A
	Max Current	Cooling	A	8.8	12.0	15.2
		Heating	A	N.A	N.A	N.A
Max Power input	Cooling	W	1700	2500	3215	
	Heating	W	N.A	N.A	N.A	
Refrigerating System	Refrigerant	R410A/460g				
	Refrigerant Connections	Liquid	inches	1/4"	1/4"	1/4"
		Suction	inches	3/8"	3/8"	1/2"
		Maximum Length	(FT / M)	66 / 20	82 / 25	82 / 25
		Maximum Height	(FT / M)	27 / 8	33 / 10	33 / 10
	Compressor	Type	Rotary			
Model		ASM125N01VDZB	ASL152DG-C7EU1	ASH201DG-C8LUL		
MFG		GMCC	HIGHLY	HIGHLY		
Fan System	Indoor air circulation (Cooling)	m ³ /h	540	710	1000	
	Indoor fan type	Cross flow				
	Indoor fan speed H/M/L	Cooling	rpm	1270/1170/1050/900/850	1250/1200/1100/900/800	1280/1200/1050/900/780
		Heating	rpm	N.A	N.A	N.A
		Dry	rpm	1270	1250	1280
		Sleep	rpm	900	900	900
	Indoor fan motor output	w	20	23	48	
	Outdoor fan type	Propeller				
	Outdoor fan speed	rpm	860	860	860	
	Outdoor fan motor output	W	31	31	70	
Others	Suitable area	m ²	15~23	20~35	30~50	
	Net dimensions (W x D x H)	Indoor	mm	777×250×201	910×294×206	1010×315×220
		Outdoor	mm	777×290×498	817×300×553	886×357×605
	Net weight	Indoor	kg	7	10	13
		Outdoor	kg	24	33	40
	Packing dimensions (W x D x H)	Indoor	mm	840×315×260	979×372×277	1096×390×297
Outdoor		mm	818×325×520	858×356×585	910×392×633	
Gross weight with pipe	Indoor	kg	9	13	16	
	Outdoor	kg	27	38	46	